







5th CLASS BOILERS AND ECODESIGN

www.**DEFRO**.pl

SIGMA E | 12-48 kW



Ecodesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: eco-pea coal 5-25 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Sensor indicating opened cover of the fuel tank;





Heat exchanger made of certified high-grade steel;



Feeder screw made of one element;



High thermal efficiency reaching 90% due to increased heat recovery from flue gases;



Changing the direction of door opening (does not apply to the inner door);



Controller K1P v4 with colour touch panel servicing four pumps /central heating, domestic hot water, circulation, floor pump/. Servicing of mixing valve. Possibility to control using GSM or INTERNET - extra paid option; adjustable position angle of the control panel;



CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



NZ version - adapted for installation in closed system, reinforced design, built-in cooling coil - extra paid option;



Energy-saving high-efficiency motoreducer with an autoreverse in the case of a fuel feeder lock;



Combustion chamber with highly effective new-generation retort burner (solution submitted to the Patent Office of the Republic of Poland);



Mechanical heat exchanger cleaning system;



Ceramic catalysts stabilising combustion process;



Pressure equalisation system in fuel container;



K1PV4 CONTROLLER




RETORT BURNER

of next-generation submitted to patent protection




ABM MOTOREDUCER




SIGMA E

	BOILER DIMENSIONS IN MM										
Dimension	12 kW	16 kW	20 kW	24 kW	36 kW	48 kW					
А	130	130	130	130	130	130					
В	775	940	920	1070	1115	1330					
С	Ø 159	Ø 159	Ø 178	Ø 178	Ø 178	Ø 194					
D	1115	1280	1280	1430	1490	1710					
E	1225	1385	1385	1535	1595	1815					
F	1405	1405	1405	1405	1485	1685					
G	825	825	865	865	965	965					
Н	115	115	115	115	115	115					
- 1	1065	1065	1110	1110	1210	1210					
J	605	605	605	574	705	705					
K	640	640	640	640	640	640					
L	1360	1360	1360	1360	1460	1460					

BOILER EQUIPMENT / PRODUCT TYPE C									
Name	standard equipment								
controller K1Pv4	yes								
ADAPTIVE CONTROL control system	yes								
PID function	yes								
GSM module	no								
INTERNET module	no								
WIFI INTERNET module	no								
levelling legs	yes								
"Fire Fighter" fire suppression system	no								
NZ version for closed system	no								
DK LOGIC 100 regulator	no								
room controller DEFRO SPK Lux	no								
ST-292 v3 room controller	no								
ST-292 v2 room controller	no								
DEFRO MZ module	no								
SPK Lux wireless regulator	no								
set for wireless communication RS	no								
system for mechanical cleaning of heat exchanger	yes								







TECHNI	CAL DAT	A OF THE	BOILER /	PRODUCT	GROUP A	· \	
Specification / boiler type	unit	12	16	20	24	36	48
Fuel			e	co-pea coa	al 5-25 mm		
5 class according to PN-EN 303:5-2012	-	✓	~	✓	~	~	✓
Ecodesign	-	✓	✓	✓	✓	✓	✓
Power range	kW	3,6-12	4,8-16	6-20	7,2-24	10,8-36	14,4-48
Heating area	m ²	1,9	2,3	2,7	3,1	4,3	5,2
Area of heated rooms ¹	m²	to 220	to 260	to 290	to 350	to 450	to 600
Capacity of fuel container ²	kg	~165	~165	~165	~165	~191	~266
Optimum thermal efficiency	%			~90,1	-90,7		
Energy efficiency class	-	С	В	В	В	В	В
Max. permissible work pressure	bar		1,5 - open	ed system,	2,5 - close	ed system	
Required flue gas draught	mbar	0,22	0,24	0,26	0,28	0,31	0,34
Water temperature on supply max.	°C			65/	80		
Boiler weight ³	kg	400	449	515	523	657	728
Boiler water tank capacity	1	88	104	110	124	170	200
Chimney section	cmxcm	14x14	14x14	16x16	16x16	18x18	22x22
Chimney section	Ø mm	160	160	180	180	200	250
Minimum chimney height	m	5	6	7	7,5	9	10
Supply and return socket diameter	mm	G1 ½"					
Diameter of the exhaust gas socket	mm	159	159	178	178	178	194
Supply	V/Hz			~230	0/50		

- ¹ Maximum area of heated rooms estimated for unit heat demand q=80 W/m².
- ² Fuel tank capacity for bulk density of eco-pea coal equal to 0,8 kg/dm³.
- ³ Boiler weight depends on its additional equipment.

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

ATTENTION! When ordering the SIGMA E boiler the customer should specify on which side the container should be located (right or left).

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

SIGMA EKOPELL | 12-20 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Mechanical heat exchanger cleaning system;





Heat exchanger made of certified high-grade steel;



ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



High thermal efficiency reaching 93% due to increased heat recovery from flue gases;



Ceramic catalysts stabilising combustion process:



APC 3 ADAPTIVE CONTROL 3 servicing six pumps /central heating, domestic hot water, circulating, floor/. Control of two mixing valves; preview and change of parameters of the main controller ONLINE through built-in internet module with RJ-45 connector;



Fuel self-ignition system;



NZ version - adapted for installation in closed system, reinforced design, built-in cooling coil - extra paid option;



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



Pellet burner with automatic cleaning function in standard;



Twin Spark System- pellet burner equipped with two igniters as a standard - option available for all powers;



Fuel reserve sensor in container stops boiler operation at minimum fuel level. After fuel recharging it is not necessary to repeat firing procedure and the boiler switches to automatic operation;



APC 3 CONTROLLER



PFI I FT BURNER




ADAPTIVE CONTROL





SIGMA EKOPELL

	BOILER DIMENSIONS IN MM								
Dimension	12 kW	16 kW	20 kW						
A	163	163	163						
В	740	901	1042						
С	Ø 159	Ø 159	Ø 178						
D	1080	1240	1390						
E	1200	1362	1510						
F	1360	1360	1360						
G	1330	1330	1330						
Н	825	825	825						
1	115	115	115						
J	1080	1080	1080						
K	1400	1400	1400						
L	1355	1355	1355						
М	675	675	675						

BOILER EQUIPMENT / PRODUCT TYPE C								
Name	standard equipment							
APC 3 ADAPITVE CONTROL controller	yes							
ADAPTIVE CONTROL control system	yes							
PID function	yes							
GSM module	no							
INTERNET module	yes							
WIFI INTERNET module	no							
levelling legs	yes							
NZ version for closed system	no							
igniter	yes							
DK LOGIC 100 regulator	no							
room controller DEFRO SPK Lux	no							
ST-292 v3 room controller	no							
ST-292 v2 room controller	no							
DEFRO MZ module	no							
SPK Lux wireless regulator	no							
set for wireless communication RS	no							
exhaust fan	yes							
system for mechanical cleaning of heat exchange	ger yes							
pellet burner with automatic cleaning functi	ion yes							







TECHNICAL DATA C	TECHNICAL DATA OF THE BOILER / PRODUCT GROUP A					
Specification / boiler type	unit	12	16	20		
Fuel	-	wood p	ellet with diamete	er 6 mm		
5 class according to PN-EN 303:5-2012	-	✓	✓	✓		
Ecodesign	-	✓	✓	✓		
Power range	kW	3,6-12	4,8-16	6,0-20		
Heating area	m²	1,7	2,1	2,5		
Area of heated rooms 1	m²	to 180	to 250	to 270		
Capacity of fuel container ²	kg	~200	~200	~200		
Optimum thermal efficiency	%	~89,1 - 93,8				
Energy efficiency class	-	A+	A+	A+		
Max. permissible work pressure	bar	1,5 - opened system, 2,5 - closed system				
Required flue gas draught	mbar	0,22	0,24	0,26		
Water temperature on supply max.	°C		65/80			
Boiler weight ³	kg	339	425	453		
Boiler water tank capacity	ı	92	100	120		
Chimney section	cmxcm	14x14	14x14	16x16		
Chimney section	Ø mm	160	160	180		
Minimum chimney height	m	5	6	7,5		
Supply and return socket diameter	mm		G1 ½"			
Diameter of the exhaust gas socket	mm	159	159	178		
Supply	V/Hz		~230/50			

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

ATTENTION! When ordering the SIGMA EKOPELL boiler the customer should specify on which side the container should be located (right or left).

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

 $^{^2}$ Fuel tank capacity for pellet bulk density 0,6 kg/dm 3 . Boiler weight depends on its additional equipment.

DEFRO KOMPAKT EKOPELL | 16-50 kW |



EcoDesign requirements fulfilled for power 16, 30 and 50kW.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



F Version -version with automatic cleaning and ash removal





Heat exchanger made of certified high-grade steel;



(extra payable according to the price list of boiler equipment)





ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



High thermal efficiency reaching 93% due to increased heat recovery from flue gases;



Ceramic catalysts stabilising combustion process:



APC 3 ADAPTIVE CONTROL 3 servicing six pumps /central heating, domestic hot water, circulating, floor/. Control of two mixing valves; preview and change of parameters of the main controller ONLINE through built-in internet module with RJ-45 connector;



Fuel self-ignition system;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler:



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



Pellet burner with automatic cleaning function in standard;



Twin Spark System- pellet burner equipped with two igniters as a standard - option available for all powers;



Fuel reserve sensor in container stops boiler operation at minimum fuel level. After fuel recharging it is not necessary to repeat firing procedure and the boiler switches to automatic operation:



APC 3 CONTROLLER



PFI I FT BURNER



ADAPTIVE CONTROL



DEFRO KOMPAKT EKOPELL F


version with automatic cleaning and ash removal (extra payable according to the price list of boiler equipment)





DEFRO KOMPAKT EKOPELL

	BOILER DIMENSIONS IN MM									
Dimension	16 kW	22 kW	30 kW	40 kW	50 kW					
А	600	600	650	700	750					
В	600	600	650	700	750					
С	1031	1180	1281	1501	1556					
D	Ø 127	Ø 127	Ø 127	Ø 127	Ø 127					
E	1002	1152	1292	1502	1566					
F	330	330	380	430	480					
G	135	135	135	135	135					
Н	125	125	125	125	128					
1	155	155	155	155	155					
J	881	1031	1050	1351	1401					
K	822	872	931	982	1021					
L	1465	1545	1630	1670	1684					

BOILER EQUIPMENT / PRODU	JCT TYPE C
Name	standard equipment
sterownik APC 3 ADAPTIVE CONTROL	yes
ADAPTIVE CONTROL control system	yes
PID function	yes
GSM module	no
INTERNET module	yes
WIFI INTERNET module	no
levelling legs	yes
NZ version for closed system	yes
igniter	yes
DK LOGIC 100 regulator	no
room controller DEFRO SPK Lux	no
ST-292 v3 room controller	no
ST-292 v2 room controller	no
DEFRO MZ module	no
SPK Lux wireless regulator	no
set for wireless communication RS	no
automatic cleaning and ash removal system	no
exhaust fan	yes
system for mechanical cleaning of heat exchanger	yes
pellet burner with automatic cleaning function	yes







TECHNICAL DATA OF THE BOILER / PRODUCT GROUP A									
Specification / boiler type	unit	16	22	30	40	50			
Fuel	-	- wood pellet with diameter 6 mm							
5 class according to PN-EN 303:5-2012	-	✓	✓	~	✓	~			
Ecodesign	-	✓	-	✓	-	✓			
Power range	kW	4,8-16	6,6-22	9,0-30	12,0-40	15,0-50			
Heating area	m²	2,0	2,4	3,2	4,2	5,0			
Area of heated rooms ¹	m²	to 210	to 290	to 400	to 530	to 660			
Capacity of fuel container ²	kg	~105	~145	~192	~289	~320			
Optimum thermal efficiency	%			~90,6-93,2					
Energy efficiency class	-	A+	A+	A+	A+	A+			
Max. permissible work pressure	bar			1,5					
Required flue gas draught	mbar	0,15	0,15	0,20	0,25	0,30			
Water temperature on supply max.	°C			65/85					
Boiler weight ³	kg	418	474	565	703	798			
Boiler water tank capacity	ı	77	98	127	180	192			
Chimney section	cmxcm	14x14	15x15	16x16	19x19	20x20			
Chimney section	Ø mm	160	170	180	210	230			
Minimum chimney height	m	5	5,5	6	6,5	7			
Supply and return socket diameter	mm	nm G1 ½"							
Diameter of the exhaust gas socket	mm	127	127	127	127	127			
Supply	V/Hz	~230/50							

- Maximum area of heated rooms estimated for unit heat demand q=75 W/m².
 Fuel tank capacity for pellet bulk density 0,6 kg/dm³.
 Boiler weight depends on its additional equipment.

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

SMART EKOPELL | 12-38 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;





Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 90% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC 3 ADAPTIVE CONTROL 3 servicing six pumps /central heating, domestic hot water, circulating, floor/. Control of two mixing valves; preview and change of parameters of the main controller ONLINE through built-in internet module with RJ-45 connector:



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler:



Twin Spark System- pellet burner equipped with two igniters as a standard - option available for all powers;



Pellet burner with automatic cleaning function in standard;



Fuel reserve sensor in container stops boiler operation at minimum fuel level. After fuel recharging it is not necessary to repeat firing procedure and the boiler switches to automatic operation;



APC 3 CONTROLLER



PELLET BURNER




ADAPTIVE CONTROL





SMART EKOPELL

	BOILER DIMENSIONS IN MM									
Dimension	12 kW	16 kW	20 kW	24 kW	28 kW	38 kW				
A1 A2 A3	156 844 126	156 844 126	156 844 126	156 844 126	156 953 126	156 1063 126				
В	552	602	602	602	602	602				
С	650	650	650	650	650	650				
D	1421	1421	1421	1421	1421	1421				
E	1012	1012	1012	1012	1121	1231				
F	1135	1135	1135	1135	1244	1354				
G	961	961	961	961	1090	1240				
Н	1361	1361	1361	1361	1361	1361				
1	238	238	238	238	284	284				
J	701	701	761	831	831	831				
K	Ø 127	Ø 127	Ø 127	Ø 127	Ø 127	Ø 127				
L	1352	1372	1435	1535	1568	1621				
М	1210	1260	1260	1260	1260	1260				

BOILER EQUIPMENT / PRO	DUCT TYPE C
Name	standard equipment
APC 3 ADAPTIVE CONTROL controller	yes
ADAPTIVE CONTROL control system	yes
PID function	yes
GSM module	no
INTERNET module	yes
WIFI INTERNET module	no
levelling legs	yes
NZ version for closed system	yes
igniter	yes
DK LOGIC 100 regulator	no
room controller DEFRO SPK Lux	no
ST-292 v3 room controller	no
ST-292 v2 room controller	no
DEFRO MZ module	no
SPK Lux wireless regulator	no
set for wireless communication RS	no
exhaust fan	yes
pellet burner with automatic cleaning function	yes







TECH	TECHNICAL DATA OF THE BOILER / PRODUCT GROUP A								
Specification / boiler type	unit	12	16	20	24	28	38		
Fuel	-		wood	d pellet with	diameter 6	3 mm			
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓	✓	✓		
Ecodesign	-	✓	✓	✓	✓	✓	✓		
Power range	kW	3,6-12	4,8-16	6,0-20	7,2-24	8,4-28	11,4-38		
Heating area	m²	1,6	1,8	2,2	2,6	3,2	3,6		
Area of heated rooms 1	m²	to 150	to 200	to 250	to 300	to 350	to 475		
Capacity of fuel container ²	kg	~195	~195	~195	~195	~195	~195		
Optimum thermal efficiency	%	~88,3-90,1							
Energy efficiency class	-	A+	A+	A+	A+	A+	A+		
Max. permissible work pressure	bar			2	,5				
Required flue gas draught	mbar	0,20	0,22	0,24	0,26	0,28	0,29		
Water temperature on supply max.	°C			65,	/80				
Boiler weight ³	kg	374	396	424	451	493	528		
Boiler water tank capacity	- 1	51	57	64	73	86	98		
Chimney section	cmxcm	14x14	14x14	14x14	15x15	16x16	18x18		
Chimney section	Ø mm	160	160	160	170	180	200		
Minimum chimney height	m	6	6,5	7	7,5	8	9		
Supply and return socket diameter	mm	G1 ½"							
Diameter of the exhaust gas socket	mm	127	127	127	127	127	127		
Supply	V/Hz	~230/50							

- ¹ Maximum area of heated rooms estimated for unit heat demand q=80 W/m².
- 2 Fuel tank capacity for pellet bulk density 0,6 kg/dm 3 . Boiler weight depends on its additional equipment.

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

DELTA EKOPELL |10-25 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 95% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC K SLIM ADAPTIVE CONTROL servicing three pumps /central heating, domestic hot water, floor/. Control of one mixing valve; preview and change of parameters of the main ONLINE controller - extra payable option;



Pellet burner with automatic cleaning function in standard;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Compact dimensions;




APC 3 SLIM CONTROLLER



PELLET BURNER




ADAPTIVE CONTROL





DELTA EKOPELL

	BOILER DIMENSIONS IN MM						
Dimension	10 kW	15 kW	20 kW	25 kW			
A1/A2	124/104	124/104	124/104	124/104			
В	609	609	691	691			
С	Ø 159	Ø 159	Ø 159	Ø 159			
D	903	903	985	985			
Е	1083	1083	1165	1165			
F	1314	1314	1314	1314			
G	1275	1275	1275	1325			
Н	730	804	844	844			
1	434	434	434	464			
J	1262	1331	1373	1406			
K	1248	1248	1248	1248			
L	470	470	470	520			
М	714	714	714	714			

BOILER EQUIPMENT / PRODUCT TYPE C						
Name	standard equipment					
sterownik APC K Slim	yes					
ADAPTIVE CONTROL control system	yes					
PID function	yes					
GSM module	no					
INTERNET module	no					
WIFI INTERNET module	no					
levelling legs	yes					
igniter	yes					
DK LOGIC 100 regulator	no					
room controller DEFRO SPK Lux	no					
ST-292 v3 room controller	no					
ST-292 v2 room controller	no					
DEFRO MZ module	no					
SPK Lux wireless regulator	no					
set for wireless communication RS	no					
pellet burner with automatic cleaning function	yes					







TECHNICAL DATA OF THE BOILER / PRODUCT GROUP D							
Specification / boiler type	unit	10	15	20	25		
Fuel	-	wood	d pellet with	diameter 6	3 mm		
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓		
Ecodesign	-	✓	✓	✓	✓		
Power range	kW	3,0-10	4,5-15	6,0-20	7,5-25		
Heating area	m ²	1,8	1,9	2,2	2,5		
Area of heated rooms ¹	m ²	to 130	to 180	to 210	to 250		
Capacity of fuel container ²	kg	~195	~195	~195	~195		
Optimum thermal efficiency	%	~90,7-95,3					
Energy efficiency class	-	A+	A+	A+	A+		
Max. permissible work pressure	bar	1,5					
Required flue gas draught	Pa	20	24	26	28		
Water temperature on supply max.	°C		65.	/80			
Boiler weight ³	kg	321	327	353	360		
Boiler water tank capacity	ı	54	60	70	75		
Chimney section	cmxcm	14x14	14x14	14x14	15x15		
Chimney section	Ø mm	160	160	160	170		
Minimum chimney height	m	5,5	6,5	7	7,5		
Supply and return socket diameter	mm	G1 ½"					
Diameter of the exhaust gas socket	mm	159 159 159 159					
Supply	V/Hz	~230/50					

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

¹ Maximum area of heated rooms estimated for unit heat demand q=100 W/m².

² Fuel tank capacity for pellet bulk density 0,6 kg/dm³.
³ Boiler weight depends on its additional equipment.

HG 25 | 23 kW



EcoDesign requirements fulfilled for power 23 kW.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for 23 kW power.

Fuel: Chunks of wood with 12 cm diameter and maximum moisture 20%.



3 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Two-stage combustion process - fuel gasification and pyrolysis;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 90% due to increased heat recovery from flue gases;



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



 $\mbox{HG 2 PID}$ controller servicing buffer, 3 pumps, mixing valve and exhaust fan;



System for mechanical cleaning of heat exchanger;



Boiler adapted for installation in closed system;



HG 2 PID CONTROLLER










HG 25

	BOILER DIMENSIONS IN MM
Dimension	23 kW
А	680
В	775
С	1210
D	1220
E	1159
F	127
G	1175
Н	1440
1	145

BOILER EQUIPMENT / PRODUCT TYPE C							
Name	standard equipment						
HG 2PID controller	yes						
GSM module	no						
PID function	yes						
levelling legs	yes						
sterownik DK LOGIC 100	no						
ST-292 v3 room controller	no						
ST-292 v2 room controller	no						
NZ version for closed system	yes						
exhaust fan	yes						
system for mechanical cleaning of heat exchanger	yes						







TECHNICAL DATA OF	THE BOILER / P	RODUCT GROUP A
Specification / boiler type	unit	HG 25 (23 kW)
Fuel	-	chunks of wood with 12 cm diameter and maximum moisture 20%.
5 class according to PN-EN 303:5-2012	-	✓
Ecodesign	-	✓
Heating area	m²	2,6
Area of heated rooms 1	m²	to 230
Capacity of fuel container	kg	~93
Optimum thermal efficiency	%	~90
Energy efficiency class	-	A+
Max. permissible work pressure	bar	2,0 - opened system, 2,5 - closed system
Required flue gas draught	mbar	0,20
Water temperature on supply max.	°C	65/85
Boiler weight ²	kg	542
Boiler water tank capacity	1	172
Chimney section	cmxcm	16x16
Chimney section	Ømm	180
Minimum chimney height	m	6
Supply and return socket diameter	mm	G1 ½"
Diameter of the exhaust gas socket	mm	127
Supply	V/Hz	~230/50
Dimensions of charging chamber and fuel charging hole	width depth height width x height	330 568 498 330x284

- ¹ Maximum area of heated rooms estimated for unit heat demand q=100 W/m².
- ² Boiler weight depends on its additional equipment.

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Cooperation with storage container is required.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

EKO SLIM | 10-30 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 93% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC 3 SLIM ADAPTIVE CONTROL servicing three pumps /central heating, domestic hot water, floor/. Control of one mixing valve; preview and change of parameters of the main ONLINE controller - extra payable option;



Pellet burner with automatic cleaning function in standard;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Compact dimensions;



APC 3 SLIM CONTROLLER



PELLET BURNER






EKO SLIM





EKO SLIM

BOILER DIMENSIONS IN MM						
Dimension	10 kW	15 kW	20 kW	25 kW	30 kW	
А	120	120	120	120	120	
В	190	190	190	190	190	
С	583	567	612	618	590	
D	Ø 127	Ø 159	Ø 159	Ø 159	Ø 159	
Е	840	840	925	925	925	
F	1615	1615	1650	1650	1650	
G	1615	1615	1650	1650	1650	
Н	325	325	325	365	365	
1	705	915	915	855	855	
J	600	600	700	700	800	

BOILER EQUIPMENT / PRODUCT TYPE C						
Name	standard equipment					
APC 3 Slim controller	yes					
ADAPTIVE CONTROL control system	yes					
PID function	yes					
GSM module	no					
INTERNET module	no					
WIFI INTERNET module	no					
levelling legs	yes					
igniter	yes					
DK LOGIC 100 room controller	no					
room controller DEFRO SPK Lux	no					
ST-292 v3 room controller	no					
ST-292 v2 room controller	no					
DEFRO MZ module	no					
SPK Lux wireless regulator	no					
set for wireless communication RS	no					
pellet burner with automatic cleaning function	yes					
platform	no					







TECHNICAL DATA OF THE BOILER / PRODUCT GROUP D						
Specification / boiler type	unit	10	15	20	25	30
Fuel	-	- wood pellet with diameter 6 mm				
5 class according to PN-EN 303:5- 2012	-	✓	✓	✓	~	✓
Ecodesign	-	✓	✓	✓	✓	✓
Power range	kW	3,0-10	4,5-15	6,0-20	7,5-25	9-30
Heating area	m ²	1,5	2,1	2,5	2,7	3,3
Area of heated rooms 1	m ²	to 160	to 220	to 270	to 355	to 425
Capacity of fuel container ²	kg	~110	~131	~137	~137	~159
Optimum thermal efficiency	%			~90,2-93	,9	
Energy efficiency class	-	A+	A+	A+	A+	A+
Max. permissible work pressure	bar	1,5 -	opened s	ystem, 2,	5 - closed s	system
Required flue gas draught	mbar	0,20	0,24	0,26	0,28	0,30
Water temperature on supply max.	°C			65/80		
Boiler weight ³	kg	288	336	380	368	402
Boiler water tank capacity	1	48	69	130	97	110
Chimney section	cmxcm	14x14	14x14	14x14	16x16	18x18
Chimney section	Ø mm	160	160	160	180	200
Minimum chimney height	m	5	6	7	7	7
Supply and return socket diameter	cal	GZ 1 1/4" / GW 1 1/4"				
Diameter of the exhaust gas socket	mm	127	159	159	159	159
Supply	V/Hz	~230/50				

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

 $^{^2}$ Fuel tank capacity for pellet bulk density 0,6 kg/dm 3 . Boiler weight depends on its additional equipment.

BIO SLIM | 10-30 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



STEEL





Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 93% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC 3 ADAPTIVE CONTROL 3 servicing six pumps /central heating, domestic hot water, circulating, floor/. Control of two mixing valves; preview and change of parameters of the main controller ONLINE through built-in internet module with RJ-45 connector:



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler:



Twin Spark System- pellet burner equipped with two igniters as a standard - option available for all powers;



Pellet burner with automatic cleaning function in standard;



Fuel reserve sensor in container stops boiler operation at minimum fuel level. After fuel recharging it is not necessary to repeat firing procedure and the boiler switches to automatic operation;



APC 3 CONTROLLER



PELLET BURNER



ADAPTIVE CONTROL




BIO SLIM





BIO SLIM

BOILER DIMENSIONS IN MM							
Dimension	10 kW	15 kW	20 kW	25 kW	30 kW		
А	120	120	120	120	120		
В	190	190	190	190	190		
С	583	567	612	618	590		
D	Ø 127	Ø 159	Ø 159	Ø 159	Ø 159		
Е	840	840	925	925	925		
F	1615	1615	1650	1650	1650		
G	1615	1615	1650	1650	1650		
Н	325	325	325	365	365		
1	705	915	915	855	855		
J	600	600	700	700	800		

BOILER EQUIPMENT / PRODUCT TYPE C					
Name	standard equipment				
APC 3 ADAPTIVE CONTROL controller	yes				
ADAPTIVE CONTROL control system	yes				
PID function	yes				
GSM module	no				
INTERNET module	yes				
WIFI INTERNET module	no				
levelling legs	yes				
igniter	yes				
DK LOGIC 100 regulator	no				
room controller DEFRO SPK Lux	no				
ST-292 v3 room controller	no				
ST-292 v2 room controller	no				
DEFRO MZ module	no				
SPK Lux wireless regulator	no				
set for wireless communication RS	no				
exhaust fan	yes				
pellet burner with automatic cleaning function	yes				
platform	no				







TECHNICAL DATA OF THE BOILER / PRODUCT GROUP D						
Specification / boiler type	J.m.	10	15	20	25	30
Fuel	-		wood pell	et with dia	meter 6 mr	n
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓	✓
Ecodesign	-	✓	✓	✓	✓	✓
Power range	kW	3,0-10	4,5-15	6,0-20	7,5-25	9-30
Heating area	m²	1,5	2,1	2,5	2,7	3,3
Area of heated rooms ¹	m²	to 160	to 220	to 270	to 355	to 425
Capacity of fuel container ²	kg	~110	~131	~137	~137	~159
Optimum thermal efficiency	%	~90,2-93,9				
Energy efficiency class	-	A+	A+	A+	A+	A+
Max. permissible work pressure	bar	1,5 -	opened s	ystem, 2,	5 - closed s	system
Required flue gas draught	mbar	0,20	0,24	0,26	0,28	0,30
Water temperature on supply max.	°C			65/80		
Boiler weight ³	kg	288	336	380	368	402
Boiler water tank capacity	ı	48	69	130	97	110
Chimney section	cmxcm	14x14	14x14	14x14	16x16	18x18
Chimney section	Ø mm	160	160	160	180	200
Minimum chimney height	m	5	6	7	7	7
Supply and return socket diameter	cal	GZ 1 ¼" / GW 1 ¼"				
Diameter of the exhaust gas socket	mm	127 159 159 159 159				159
Supply	V/Hz	~230/50				

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

 $^{^2}$ Fuel tank capacity for pellet bulk density 0,6 kg/dm 3 . Boiler weight depends on its additional equipment.

KOMFORT EKO | 9-40 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: eco-pea coal 5-25 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Optional horizontal or vertical outlet of flue gas - CG option;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 92% due to increased heat recovery from flue gases;



Combustion chamber with highly effective retort burner;



Controller servicing two pumps /central heating, domestic hot water/. Cooperates





Changing the direction of door opening (does not apply to the inner door);




Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler:




MASTER 300 RS CONTROLLER






KOMFORT EKO

BOILER DIMENSIONS IN MM									
Dimension	9 kW	12 kW	15 kW	20 kW	25 kW	30 kW			
А	482	482	482	532	532	582			
В	540	540	540	640	640	640			
С	1368	1368	1433	1483	1528	1528			
D	1029	1029	1093	1148	1159	1160			
Е	Ø 159	Ø 159	Ø 159	Ø 178	Ø 178	Ø 178			
F	535	535	605	645	715	735			
G	891	891	962	1001	1072	1092			



BOILER EQUIPMENT / PRODUCT TYPE C								
Name	standard equipment							
Master 300 RS controller	yes							
levelling legs	yes							
NZ version for closed system	yes							
DK LOGIC 100 regulator	no							
DK MATIC valve module	no							
DKMZ module	no							



Specification / boiler type	J.m.	9	12	15	20	25	30	40
Power range	kW	2,7-9	3,6-12	4,5-15	6,0-20	7,5-25	9,0-30	12,0
5 class according to PN- EN 303:5-2012	-	✓	✓	~	~	✓	✓	~
Ecodesign	-	✓	✓	✓	✓	✓	✓	✓
Heating area	m ²	1,5	1,6	2,0	2,4	2,8	3,2	4,0
Area of heated rooms ¹	m²	to 115	to 150	to 190	to 250	to 315	to 375	to 50
Capacity of fuel container 2	kg	~132	~132	~132	~191	~191	~191	~25
Optimum thermal efficiency	%	~89,9-92,5						
Energy efficiency class	-	С	В	В	В	В	В	В
Max. permissible work pressure	bar				1,5			
Required flue gas draught	mbar	0,19	0,22	0,24	0,26	0,28	0,23	0,3
Water temperature on supply max.	°C				65/80			
Boiler weight ³	kg	394	394	445	514	553	611	754
Boiler water tank capacity	1	64	68	82	97	112	123	150
Chimney section	cmxcm	14x14	14x14	14x14	16x16	16x16	17x17	19x
Chimney section	Ø mm	160	160	160	180	180	190	220
Minimum chimney height	m	5	5,5	6	6,5	7	7,5	8
Width	mm	1116	1116	1111	1228	1228	1278	131
Depth (CT)	mm	891	891	962	1001	1072	1092	119
Depth (CG)	mm	707	707	768	817	888	908	100
Height (CG)	mm	1448	1448	1517	1563	1608	1608	161
Supply and return socket diameter	cal				1 ½ "			
Release socket diameter	cal				1/2 "			
Diameter of the exhaust gas socket	mm	159	159	159	178	178	178	194

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

ATTENTION! When ordering KOMFORT EKO boiler the customer should specify on which side the container should be located (right or left). It is also necessary to specify location of the flue during ordering - from top or in the rear wall of the boiler.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

² Fuel tank capacity for bulk density of eco-pea coal equal to 0,8 kg/dm³.

³ Boiler weight depends on its additional equipment.

KOMFORT EKO LUX | 9-40 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: eco-pea coal 5-25 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Optional horizontal or vertical outlet of flue gas - CG option;





Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 92% due to increased heat recovery from flue gases;



Combustion chamber with highly effective retort burner;



Controller K1P v4 with colour touch panel servicing four pumps /central heating, domestic hot water, circulation, floor pump/. Servicing of mixing valve. Possibility to control using GSM or INTERNET - extra paid option; adjustable position angle of the control panel;



Changing the direction of door opening (does not apply to the inner door):



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Sensor indicating opened cover of the fuel tank;



Pressure equalisation system in fuel container;



Feeder screw made of one element:

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Energy-saving high-efficiency motoreducer with an autoreverse in the case of a fuel feeder lock;




K1PV4 CONTROLLER



RETORT BURNER




ABM MOTOREDUCER




KOMFORT EKO LUX

BOILER DIMENSIONS IN MM										
Dimension	9 kW	12 kW	15 kW	20 kW	25 kW	30 kW				
А	482	482	482	532	532	582				
В	540	540	540	640	640	640				
С	1368	1368	1443	1483	1528	1528				
D	1029	1029	1093	1148	1159	1160				
E	Ø 159	Ø 159	Ø 159	Ø 178	Ø 178	Ø 178				
F	535	535	605	645	715	735				
G	891	891	962	1001	1072	1092				



BOILER EQUIPMENT / PRODUCT TYPE C						
Name	standard equipment					
controller K1Pv4	yes					
ADAPTIVE CONTROL control system	yes					
PID function	yes					
GSM module	no					
INTERNET module	no					
WIFI INTERNET module	no					
levelling legs	yes					
NZ version for closed system	yes					
room controller DEFRO SPK Lux	no					
ST-292 v3 room controller	no					
ST-292 v2 room controller	no					
DEFRO MZ module	no					
SPK Lux wireless regulator	no					
set for wireless communication RS	no					



TECHN	ICAL DA	ATA OF TI	HE BOILE	R / PRO	DUCT GI	ROUP A		
Specification / boiler type	J.m.	9	12	15	20	25	30	40
Power range	kW	2,7-9	3,6-12	4,5-15	6,0-20	7,5-25	9,0-30	12,0-40
5 class according to PN- EN 303:5-2012	-	✓	✓	~	~	✓	✓	✓
Ecodesign		✓	✓	✓	✓	✓	✓	✓
Heating area	m ²	1,5	1,7	2,0	2,4	2,8	3,2	4,0
Area of heated rooms ¹	m²	to 115	to 150	to 190	to 250	to 315	to 375	to 500
Capacity of fuel container ²	kg	~132	~132	~132	~191	~191	~191	~258
Optimum thermal efficiency	%	90,5-90,7						
Energy efficiency class		С	В	В	В	В	В	В
Max. permissible work pressure	bar	1,5						
Required flue gas draught	mbar	0,19	0,22	0,24	0,26	0,28	0,23	0,32
Water temperature on supply max.	°C				65/80			
Boiler weight ³	kg	407	407	456	529	568	626	769
Pojemność wodna kotła	1	64	68	82	97	112	123	153
Chimney section	cmxcm	14x14	14x14	14x14	16x16	16x16	17x17	19x19
Chimney section	Ø mm	160	160	160	180	180	190	220
Minimum chimney height	m	5	5,5	6	6,5	7	7,5	8
Width	mm	1068	1068	1063	1228	1228	1278	1310
Depth (CT)	mm	891	891	962	1001	1062	1092	1192
Depth (CG)	mm	739	739	810	849	920	940	1040
Height (CG)	mm	1426	1426	1477	1528	1573	1573	1583
Supply and return socket diameter	cal	1 ½ "						
Release socket diameter	cal				1/2 "			
Diameter of the exhaust gas socket	mm	159	159	159	178	178	178	194

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

ATTENTION! When ordering KOMFORT EKO LUX boiler the customer should specify on which side the container should be located (right or left). It is also necessary to specify location of the flue during ordering - from top or in the rear wall of the boiler.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

² Fuel tank capacity for bulk density of eco-pea coal equal to 0,8 kg/dm³.

³ Boiler weight depends on its additional equipment.

SPECTRA | 10-25 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 94% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC K SLIM ADAPTIVE CONTROL servicing three pumps /central heating, domestic hot water, floor/. Control of one mixing valve; preview and change of parameters of the main ONLINE controller - extra payable option;



Pellet burner with automatic cleaning function in standard;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Compact dimensions;



APC K SLIM CONTROLLER



PELLET BURNER



ADAPTIVE CONTROL




SPECTRA



SPECTRA

	BOILER DIMENSIONS IN MM							
Dimension	10 kW	14 kW	20 kW	25 kW				
А	496	496	546	546				
В	1151	1151	1201	1201				
С	1376	1376	1426	1476				
D	995	995	1045	1100				
Е	Ø 159	Ø 159	Ø 159	Ø 159				
F	835	835	815	960				
G	630	630	630	770				

BOILER EQUIPMENT / PROD	DUCT TYPE C			
Name	standard equipment			
APC K Slim controller	yes			
ADAPTIVE CONTROL control system	yes			
PID function	yes			
GSM module	no			
INTERNET module	no			
WIFI INTERNET module	no			
levelling legs	yes			
igniter	yes			
room controller DEFRO SPK Lux	no			
ST-292 v3 room controller	no			
ST-292 v2 room controller	no			
DEFRO MZ module	no			
SPK Lux wireless regulator	no			
set for wireless communication RS	no			
pellet burner with automatic cleaning function	yes			





TECHNICAL DATA OF	THE BOIL	ER / PROD	UCT GROU	JP A	
Specification / boiler type	unit	10	14	20	25
Fuel		woo	od pellet with	diameter 6	mm
Power range	kW	3,0-10	4,2-14	6,0-20	7,5-25
Heating area	m²	1,5	1,8	2,3	3,0
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓
Ecodesign	-	✓	✓	✓	✓
Energy efficiency class		A+	A+	A+	A+
Area of heated rooms ¹	m ²	to 125	to 175	to 240	to 300
Capacity of fuel container ²	kg	~141	~141	~152	~199
Optimum thermal efficiency	%		~92,9	9-94,7	
Max. permissible work pressure	bar		1	,5	
Required flue gas draught	mbar	0,20	0,23	0,26	0,28
Water temperature on supply max.	°C		65	/80	
Boiler weight ³	kg	340	350	372	467
Boiler water tank capacity	1	65	63	71	103
Chimney section	cmxcm	14x14	14x14	14x14	15x15
Chimney section	Ømm	160	160	160	170
Minimum chimney height	m	6	6,5	7	7,5
Width	mm	1151	1151	1201	1201
Depth	mm	835	835	815	960
Height	mm	1396	1396	1446	1496
Supply and return socket diameter		GW 1 ½"			
Release socket diameter		1/2"	1/2"	1/2"	1/2"
Diameter of the exhaust gas socket	mm	159	159	159	159

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

¹ Maximum area of heated rooms estimated for unit heat demand g=70 W/m².

 $^{^2}$ Fuel tank capacity for pellet bulk density 0,6 kg/dm 3 . Boiler weight depends on its additional equipment.

ALFA | 12-30 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Fuel reserve sensor in container stops boiler operation at minimum fuel level. After fuel recharging it is not necessary to repeat firing procedure and the boiler switches to automatic operation;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 95% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC CENTER 3 servicing six pumps /central heating, domestic hot water, circulating, floor/. Control of two mixing valves; preview and change of parameters of the main controller ONLINE through built-in internet module with RJ-45 connector;



Central pellet burner with automatic cleaning function as a standard;



Boiler adapted for installation in closed system if the protections are assembled in accordance with the operation and maintenance manual of the boiler:



Compact dimensions;



Exhaust fan eliminating problem with chimney draught and stabilising operation of the boiler;



Automatic heat exhanger cleaning and ash removal system;



Vacuum sensor protecting against incorrect combustion process;



Hydraulic set with circulating pump and thermostatic valve as boiler protection against low return temperature;




APC CENTER CONTROLLER



ALFA

BOILER DIMENSIONS IN MM								
Dimension	12 kW	17 kW	22 kW	30 kW				
А	470	490	490	610				
В	1103	1123	1123	1325				
С	1340	1340	1495	1495				
D	1251	1271	1426	1426				
E	Ø 127	Ø 127	Ø 127	Ø 127				
F	731	731	731	771				
G	1014	1029	1029	1069				
Н	1169	1169	1324	1324				

BOILER EQUIPMENT / PRODUCT TYPE C						
Name	standard equipment					
APC CENTER controller	yes					
PID function	yes					
GSM module	no					
INTERNET module	no					
WIFI INTERNET module	no					
levelling legs	yes					
igniter	yes					
room controller DEFRO SPK Lux	no					
DEFRO MZ module	no					
SPK Lux wireless regulator	no					
ST-292 v3 room controller	no					
ST-292 v2 room controller	no					
set for wireless communication RS	no					
central pellet burner with automatic cleaning function	yes					
extra charge for PLUS version - enlarged container	no					
hydraulic kit with thermostatic valve and circulation pump	yes					



TECHNICAL DATA OF THE BOILER / PRODUCT GROUP D							
Specification / boiler type	unit	12	17	22	30		
Fuel		wood pellet with diameter 6 mm					
Power range	kW	3,6-12	5,1-17	6,6-22	9-30		
Heating area	m ²	1,3	1,7	1,9	2,7		
5 class according to PN-EN 303:5-2012		✓	✓	✓	✓		
Ecodesign		✓	✓	✓	✓		
Area of heated rooms 1	m ²	to 150	to 215	to 275	to 375		
Capacity of fuel container (STD/PLUS) ²	kg	~82/~156	~82/~156	~116/ ~210	~147/ ~229		
Optimum thermal efficiency	%		~91	,0-95,1			
Energy efficiency class	-	A+	A+	A+	A+		
Max. permissible work pressure	bar			1,5			
Required flue gas draught	mbar	0,22	0,27	0,27	0,30		
Water temperature on supply max.	°C		6	5/85			
Boiler weight ³	kg	370	380	415	510		
Boiler water tank capacity	1	60	60	70	90		
Chimney section	cmxcm	14x14	14x14	16x16	18x18		
Chimney section	Ø mm	160	160	180	200		
Minimum chimney height	m	5,5	6	6,5	7,5		
Width	mm	1103	1123	1123	1352		
Depth	mm	1014	1029	1029	1069		
Height	mm	1340	1340	1495	1495		
Supply and return socket diameter		GW 1"					
Release socket diameter		GW ½"					
Diameter of the exhaust gas socket	mm	127	127	127	127		

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

Maximum area of heated rooms estimated for unit heat demand q=80 W/m².
 Fuel tank capacity for pellet bulk density 0,6 kg/dm³.
 Boiler weight depends on its additional equipment.

OPTIMA DS | 10-30 kW



Ecodesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: hard coal assortment of pea type.

Bottom-fired boiler was submitted to patent protection in the Patent Office of Republic of Poland.



3 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Boiler is factory equipped with thermostatic draught regulator;



Heat exchanger made of certified high-grade steel;



Nozzle reducing flue gas emission (The Patent Office of Republic of Poland protection);



High thermal efficiency reaching 90% due to increased heat recovery from flue gases;



Large furnace chamber;



Mechanical adjustment of combustion process using a knob in ash-pan doors and draught regulator;




Adjustment of secondary air inflow;



Mechanical movable grate for removal of ash from grate bars;





NZ version - adapted for installation in closed system, reinforced design, cooling coil pipe installed - extra paid option;




OPTIMA DS

BOILER DIMENSIONS IN MM							
Dimension	10 kW	14 kW	19 kW	24 kW	30 kW		
А	635	685	685	735	735		
В	791	791	991	991	991		
С	Ø 178						
D	1165	1165	1365	1365	1365		
E	304	304	304	304	304		
F	1325	1325	1325	1325	1405		









TECHNICAL DAT	A OF THE	BOILER /	PRODUC	T GROUP	A	
Specification / boiler type	unit	10	14	19	24	30
Min. safe capacity of the storage container	I	1000	1400	2000	2400	2400
Energy efficiency class	-	В	В	В	В	В
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓	✓
Ecodesign	-	✓	✓	✓	✓	✓
Heating area	m²	2,4	2,6	3,3	3,6	4,3
Area of heated rooms 1	m²	to 125	to 175	to 240	to 300	to 375
Single fuel charging	kg	14	18	28	33	33
Optimum thermal efficiency	%			90		
Max. permissible work pressure	bar	1,5	- opened sy	stem, 2,5	- closed sys	tem
Required flue gas draught	mbar	0,20	0,23	0,26	0,28	0,30
Water temperature on supply max.	°C			65/90		
Boiler water tank capacity	1	72	78	98	105	117
Boiler weight ²	kg	379	413	470	511	558
Chimney section	cmxcm	16x16	16x16	16x16	16x16	18x18
Chimney section	Ø mm	180	180	180	180	200
Minimum chimney height	m	5	5	5	6	6
Width	mm	635	685	685	735	735
Depth	mm	1325	1325	1325	1325	1405
Height	mm	1165	1165	1365	1365	1365
Supply and return socket diameter				GW 1 ½ "		
Release socket diameter				1/2 "		
Diameter of the exhaust gas socket	mm	178	178	178	178	178

¹ Maximum area of heated rooms estimated for unit heat demand q=80 W/m².

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from $38\ to\ 50\ mm.$

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

Cooperation with storage container is required.

² Boiler weight depends on its additional equipment.

KOMFORT EKO PZ |12-30 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: eco-pea coal 5-25 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;



Ceramic catalysts stabilising combustion process;



Heat exchanger made of certified high-grade steel;



Combustion chamber with cast-iron burner EKO-ENERGIA;



High thermal efficiency reaching 94% due to increased heat recovery from flue gases;



Changing the direction of door opening (does not apply to the inner door);



Controller K1P v4 with panel servicing four pumps /central heating, domestic hot water, circulation, floor pump/. Servicing of mixing valve. Possibility to control using GSM or INTERNET - extra paid option; adjustable position angle of the control panel;



Feeder screw made of one element;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Pressure equalisation system in fuel container;



Vertical or horizontal configuration of the flue after the installation of the torsion bend (the torsional bend does not constitute the boiler's equipment);



Possibility of moving the fuel tank;








KOMFORT EKO PZ

	BOILER DIMENSIONS IN MM							
Dimension	12	15	20	25	30			
А	480	480	530	530	580			
В	530	530	530	530	530			
С	1145	1160	1195	1195	1205			
D	1303	1368	1418	1463	1463			
Е	1368	1433	1483	1528	1528			
F	1433	1498	1548	1593	1593			
G	1345	1445	1445	1445	1545			
H1	1204	1269	1319	1350	1350			
H2	1315	1380	1430	1475	1475			
1	159	159	159	178	178			
J	535	605	645	715	735			
K	804	874	904	974	994			
L	95	95	95	95	95			
М	140	140	140	140	140			

BOILER EQUIPMENT / PRODUCT TYPE C					
Name	standard equipment				
ST 483K controller	yes				
GSM module	no				
INTERNET module	no				
WIFI INTERNET module	no				
levelling legs	yes				
ST-292 v3 room controller	no				
ST-292 v2 room controller	no				
DEFRO MZ module	no				
SPK Lux wireless regulator	no				
room controller DEFRO SPK Lux	no				
set for wireless communication RS	no				







TECHNICAL D	TECHNICAL DATA OF THE BOILER / PRODUCT GROUP A						
Specification / boiler type	unit	12	15	20	25	30	
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓	✓	
Ecodesign	-	✓	✓	✓	✓	✓	
Energy efficiency class	-	В	В	В	В	В	
Power range	kW	3,6-12	4,5-15	6,0-20	7,8-26	9,0-30	
Heating area	m²	1,6	1,9	2,3	2,7	3,1	
Area of heated rooms 1	m²	to 150	to 190	to 250	to 325	to 375	
Capacity of fuel container 2	kg	~118	~150	~150	~171	~198	
Optimum thermal efficiency	%			- -90,7-94,7			
Max. permissible work pressure	bar			1,5			
Required flue gas draught	mbar	0,22	0,24	0,26	0,28	0,30	
Water temperature on supply max.	°C			65/80			
Boiler weight ³	kg	412	485	545	595	650	
Boiler water tank capacity	- 1	64	75	91	105	117	
Chimney section	cmxcm	14x14	14x14	16x16	16x16	18x18	
Chimney section	Ø mm	160	160	180	180	200	
Minimum chimney height	m	5,5	6	6,5	7	7	
Supply and return socket diameter	cal		GW 1½"				
Diameter of the exhaust gas socket	mm	159	159	159	178	178	

- ¹ Maximum area of heated rooms estimated for unit heat demand q=80 W/m².
- ² Fuel tank capacity for bulk density of eco-pea coal equal to 0,8 kg/dm³.
- ³ Boiler weight depends on its additional equipment.

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

Additional equipment components shall be added during ordering of the boiler because there is no possibility of installation in the future.

KOMFORT EKO EKOPELL | 14-35 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 94% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC K SLIM ADAPTIVE CONTROL servicing three pumps /central heating, domestic hot water, floor/. Control of one mixing valve; preview and change of parameters of the main ONLINE controller - extra payable option;



Pellet burner with automatic cleaning function in standard;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Vertical or horizontal configuration of the flue after the installation of the torsion bend (the torsional bend does not constitute the boiler's equipment);



APC K SLIM CONTROLLER



PELLET BURNER



ADAPTIVE CONTROL




KOMFORT EKO EKOPELL




KOMFORT EKO EKOPELL

	BOILER DIMENSIONS IN MM						
Dimension	14 kW	20 kW	25 kW	30 kW	35 kW		
А	480	480	480	530	530		
В	700	700	700	700	700		
С	1302	1302	1302	1352	1352		
D	1318	1318	1383	1433	1478		
E	1383	1383	1448	1498	1543		
F	1448	1448	1513	1563	1608		
G	1348	1348	1348	1348	1348		
H1	1218	1218	1284	1334	1365		
H2	1330	1330	1395	1445	1490		
1	159	159	159	159	178		
J	535	535	605	645	715		
K	804	804	874	914	984		



BOILER EQUIPMENT / PRODUCT TYPE C						
Name	standard equipment					
APC K Slim controller	yes					
ADAPTIVE CONTROL	yes					
PID function	yes					
GSM module	no					
INTERNET module	no					
WIFI INTERNET module	no					
levelling legs	yes					
igniter	yes					
ST-292 v3 room controller	no					
ST-292 v2 room controller	no					
DEFRO MZ module	no					
room controller DEFRO SPK Lux	no					
SPK Lux wireless regulator	no					
set for wireless communication RS	no					
central pellet burner with automatic cleaning function	yes					



TECHNICAL	DATA OF	THE BOIL	ER / PROD	UCT GROU	PΑ	
Specification / boiler type	unit	14	20	25	30	35
Power range	kW	4,2-14	6,0-20	7,5-25	9,0-30	10,5-35
5 class according to PN-EN 303:5-2012	-	✓	✓	✓	✓	✓
Ecodesign		✓	✓	✓	✓	✓
Heating area	m ²	2,1	2,3	2,6	3,2	3,6
Area of heated rooms ¹	m²	to 175	to 250	to 310	to 375	to 435
Capacity of fuel container 2	kg	~146	~146	~146	~146	~146
Optimum thermal efficiency	%			~90,5-94,9		
Energy efficiency class		A+	A+	A+	A+	A+
Max. permissible work pressure	bar			1,5		
Required flue gas draught	mbar	0,23	0,26	0,28	0,30	0,31
Water temperature on supply max.	°C			65/80		
Boiler weight ³	kg	356	367	410	466	509
Boiler water tank capacity	1	74	77	91	109	125
Chimney section	cmxcm	14x14	16x16	16x16	18x18	18x18
Chimney section	Ø mm	160	180	180	200	200
Minimum chimney height	m	5	5	6	6	7
Width	mm	1302	1302	1302	1352	1352
Depth	mm	1153	1153	1193	1193	1267
Height	mm	1448	1448	1513	1563	1608
Supply and return socket diameter	cal	1 ½ "				
Release socket diameter	cal			1/2 "		
Diameter of the exhaust gas socket	mm	159	159	159	159	178

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

ATTENTION! When ordering KOMFORT EKO EKOPELL boiler the customer should specify on which side the container should be located (right or left)

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

² Fuel tank capacity for pellet bulk density 0,6 kg/dm³.

³ Boiler weight depends on its additional equipment.

GAMMA |10-25 kW



EcoDesign requirements fulfilled for all powers.

The boiler meets the requirements of the class 5 acc. to the PN-EN 303-5:2012 for all powers.

Fuel: Wood pellet with diameter 6 mm.



5 years warranty for heat exchanger tightness, 2 years for the remaining components and efficient operation of boiler;

ADAPTIVE CONTROL

ADAPTIVE CONTROL control - adjustment of boiler operation based on air flow through the heat exchanger;



Heat exchanger made of certified high-grade steel;



Ceramic catalysts stabilising combustion process;



High thermal efficiency reaching 94% due to increased heat recovery from flue gases;



Fuel self-ignition system;



APC K SLIM ADAPTIVE CONTROL servicing three pumps /central heating, domestic hot water, floor/. Control of one mixing valve; preview and change of parameters of the main ONLINE controller - extra payable option;



Pellet burner with automatic cleaning function in standard;



Boiler adapted for installation in the closed system provided that protections were installed in accordance with the operation and maintenance manual of the boiler;



Weather control as standard;



Mechanical heat exchanger cleaning system;



Possibility of moving the fuel tank;



APC K SLIM CONTROLLER



PELLET BURNER




ADAPTIVE CONTROL




GAMMA | 10-25 kW

	BOILER DIMENSIONS IN MM						
Dimension	10 kW	15 kW	20 kW	25 kW			
А	557	557	607	657			
В	605	605	605	605			
С	1162	1162	1212	1260			
D	1345	1495	1495	1495			
E	1075	1225	1206	1206			
F	159	159	178	178			
G	617	617	617	617			
Н	100	100	100	100			

BOILER EQUIPMENT / PRODUCT TYPE C					
Name	standard equipment				
APC K Slim controller	yes				
ADAPTIVE CONTROL	yes				
PID function	yes				
system for automatical cleaning of heat exchanger	yes				
GSM module	no				
INTERNET module	no				
WIFI INTERNET module	no				
levelling legs	yes				
igniter	yes				
ST-292 v3 room controller	no				
ST-292 v2 room controller	no				
DEFRO MZ module	no				
room controller DEFRO SPK Lux	no				
SPK Lux wireless regulator	no				
set for wireless communication RS	no				
central pellet burner with automatic cleaning function	yes				





TECHNICAL DATA	OF THE E	BOILER / PR	ODUCT GRO	OUP D		
Specification / boiler type	unit	10	15	20	25	
Power range	kW	3,0-10	4,5-15	6,0-20	7,5-25	
5 class according to PN-EN 303:5- 2012	-	✓	✓	✓	✓	
Ecodesign	-	✓	✓	✓	✓	
Heating area	m ²	1,3	1,5	1,9	2,3	
Area of heated rooms 1	m ²	to 125	to 185	to 250	to 310	
Capacity of fuel container ²	kg	~146	~146	~146	~146	
Optimum thermal efficiency	%		~91,7	7-94,2		
Energy efficiency class		A+	A+	A+	A+	
Max. permissible work pressure	bar		1.	,5		
Required flue gas draught	mbar	0,20	0,24	0,26	0,28	
Water temperature on supply max.	°C		65/	/80		
Boiler weight ³	kg	~355	~375	~411	~448	
Boiler water tank capacity	1	77	96	103	111	
Chimney section	cmxcm	14x14	14x14	16x16	16x16	
Chimney section	Ø mm	160	160	180	180	
Minimum chimney height	m	5 5 6 6				
Supply and return socket diameter	cal	1 ½ "				
Release socket diameter	cal	1/2 "				
Diameter of the exhaust gas socket	mm	159	159	159	159	

Height of boiler can be additionally adjusted by means of provided levelling legs. The regulation of legs varies from 38 to 50 mm.

¹ Maximum area of heated rooms estimated for unit heat demand q=70 W/m².

 $^{^2}$ Fuel tank capacity for pellet bulk density 0,6 kg/dm³. 3 Boiler weight depends on its additional equipment.

ECOFLOW PUMP



HIGHLY EFFICIENT CIRCULATING PUMPS FOR HEATING SYSTEMS

Pumps supporting ECM technology and equipped with a rotor with permanent magnets, intended for use in central heating systems, floor heating systems, boiler systems and solar systems.

LOW RUNNING COSTS

Running costs are at the minimum level due to the highly-efficient motor with permanent magnet and electronic commutator (ECM technology) and the energy efficiency index (EEI) exceeds the level indicated in the ErP 2015 directive.

HOW TO IMPROVE EFFICIENCY?

The impressively simple design of the motor with patented Anti-Block technology (spherical-shaped shaftless motor). This solution requires only one bearing, which is self-levelling and does not require any shaft. It contributes to a considerable decrease in the number of expensive and complicated parts.

SPHERICAL ROTOR

Spherical rotor with permanent magnets is the only mobile part. The spherical motor of the pump does not have a shaft what ensures quiet operation throughout the entire service life. Separation of the magnetic compartment from liquid stream prevents jamming and damages of the pump.

EASY AND QUICK ELECTRICAL CONNECTION

Innovative plug, which is compatible with plugs of the pumps previously installed in the facility. Rotation of body motor with a ring allows setting plug in each position what ensures easy assembly.

THERMAL PROTECTION

The pumps are equipped with an internal temperature sensor as a standard. Operation of the pump between 105°C and 115°C results in a continuous decrease of speed of the pump. Pump stops automatically if the temperature reaches 125°C and restarts after cooling down to 115°C. Moreover, limitation of starting current to 6.5A protects also older and external components controlling the heating.



OPERATING MODES:



WHITE:

Stepless control of fixed rotational speed in particular for the supply of the boilers, conventional heating systems and systems with hydraulic separators;



BLUE

Automatic control of proportional pressure Δp -v, in particular for thermostatic regulating valves on the radiators;



GREEN:

Automatic control of constant pressure $\Delta p\text{-c},$ used for floor heating. Furthermore, blinking of LED informs about potential messages.

AUTOMATIC AIR BLEEDING:

Just turn the knob to air bleeding symbol for more than 5 seconds to start the automatic air bleeding function for the pump regardless which control option has been previously selected. This function allows the efficient removal of the air from the pump's interior. When this service operation is completed the pump automatically returns to all previously selected settings.

EASY TO USE

One knob controls all functions, from stepless control to automatic air bleeding. Multi-colour LED inside the transparent knob automatically shows currently selected control option.

NEW AND INNOVATIVE DESIGN

Deposits present in the pumped liquid may accumulate on fixed magnetic parts of the pump and be a cause of jamming and damage or decrease in efficiency. Ecoflow Pump is equipped with Anti-Block, separating the completely primary stream of pumped liquid from fixed magnetic parts.

Such innovative design of the Defro Ecoflow pump ensures correct and trouble-free operation even in the old heating systems.

TECHNICAL DATA						
Туре	4	6				
Range of temperature the medium ¹	0°C to +110°C					
Capacity	3,2	! m³				
Delivery head	4 m	6 m				
Maximum operating pressure	10 bar	(Pn 10)				
Power supply	200-240 V	/, 50/60 Hz				
Electrical connection	pl	ug				
IP rating of the housing	IP	44				
Insulation class	Class 155 (F)					
Operation	stepless control of constant rotational speed automatic control of proportional pressure automatic control of constant pressure					
Material	grey cast iron (EN-GJL-2	200) cataphoretic painting				
Speed range	pump automatically adapts the revolutions to demands of the system, automatic air bleeding, dry-run protec- tion, Anti-Block					
Energy Efficiency Index EEI ²	<0,21	<0,23				
Standard connectors size	G 1½"	- Rp1"				
Assembly length	180 mm	180 mm				
Appliance class	i					
Allowable pumped media ³	heating water acc. to VDI 2035, water-glycol mixture					
Weight	3 kg	3 kg				

¹ They must not freeze. To avoid condensation temperature of the medium should be always higher than ambient temperature.

² Point of reference for the most effective circulating pumps is EEI <0.20

³ The efficiency of the pump would change considerably when water-glycol mixtures with EEI higher than 20% are pumped.



PELLET BURNER



DESIGN AND INTENDED USE OF THE BURNER

The burner is a structure welded of heat-resistant steel H20N12S2. The burner is equipped with mobile grate connected with linear cylinder as a standard. This cylinder cleans furnace from the residues of ashes and sinters after each shutdown and set time. Body of the burner consists of intermediate screw-conveyor feeder, precisely dosing a dose of pellet in amounts ensuring optimum combustion conditions. Dose of air necessary for combustion is supplied by forced-draught fan to set of air nozzles designed and arranged in the furnace chamber of the burner. This solution ensures optimum oxygenation of combusted fuel and the other gases formed during combustion process. Shape of the grate was designed to achieve the best possible emission while maintaining high effectiveness of the combustion process. Automatic firing function is implemented by the ceramic heater. Burner is available in the power range from 15 to 75 kW.

FUEL QUALITY PARAMETERS

The burner is intended for combustion of wood granules with 6-8 mm diameter. Fuel - pellet made acc. to PN-EN 14961-2:2011, class C1 with the following parameters:

- granulated product diameter: 6-8 mm
- length of granulated product: 3.15-40 mm
- calorific value: >17.0 MJ/kg
- sulphur content: max. 0.03%
- moisture content: ≤12%
- ash content : ≤0.5%
- bulk density: >600 kg/m3

COMFORT AND SAFETY


Burner operates in automatic cyclic mode and is characterized with maintenance-free firing up and automatic dampening depending on parameters set. Boiler servicing is maximally limited due to use of the intuitive electronic controller for operation of boiler/burner and well thought-out design solutions. Setting of boiler operation parameters and then ongoing adding the fuel to the tank and removal of ashes formed during combustion belong to the primary operations. Particular attention should be paid to furnace self-cleaning function by mobile grate from sinters and carbon deposits formed during combustion. Furnace self-cleaning function is implemented automatically after each damping damping of the boiler or in cycles, every 6 hours (setting can be changed). Thanks to this solution, the customer can enjoy comfortable use of the boiler.

Electronic controller is responsible for automatic operation of the burner and it cooperates with, among others:

- fuel feeder
- fan
- ceramic igniter (auto ignition function)
- flame detection sensor (photoelectric cell)
- burner's thermal overload relay
- limiter of safety temperature STB.
- moreover, it is also adapted for cooperation with heating system equipment e.g. mixers, pumps, buffer, weather and room control (detailed information in controller manual)

Electronic controller and furnace are equipped with series of protections to ensure maximally safe and trouble-free operation. In case of irregularities, the alarm is activated in the form of an acoustic signal and the display shows a relevant message informing about the reason for the alarm, e.g. lack of fuel (the function performed by the fuel level sensor). Several protections are used to protest boiler/burner against damage:

- temperature alarm
- STB safety temperature limiter
- automatic control of sensors
- protection against water boiling in the boiler
- feeding pipe overheating sensor



DEFRO CONTROLLERS




APC 3 ADAPTIVE CONTROL

CONTROLLER FUNCTIONS:

- innovative control system ADAPTIVE Control using turbine flow meter ensuring optimum selection of fan and feeder operation parameters
- fan control (testing of air flow necessary for correct combustion process) and feeder
- control of central heating and domestic hot water pump as well as valves
- · control of auxiliary equipment
- control of two mixing valves with assigned circulation pumps
- control of two additional devices e.g. circulating nump, additional central heating nump.
- ting pump, additional central heating pump

 automatic firing up and damping a boiler
- · weekly programs
- control through the internet (remote firing up and damping) via www.emodul.pl
- possibility to connect room controller with RS or conventional communication e.g. SPK LUX
- . option to connect the ST-65 GSM module
- · firing up using a heater
- fuel consumption measurement using volumetric sensor installed in fuel tank as a standard
- possibility to control additional mixing valve using DEFRO MZ module
- large colour graphical display
- controller panel located in the control desk with adjustable inclination angle
- temperature sensor for central heating, domestic hot water, valves, external of return
- photoresistor (flame sensor)
- equipped with temperature protection (thermal overload relay)
- equipped with temperature protection for burner



K1PV4

CONTROLLER FUNCTIONS:

- innovative ADAPTIVE CONTROL control system using turbine flow meter ensuring optimum selection of fan and feeder operation parameters
- archive of last twenty alarm conditions of the boiler
- possibility to export temperatures history to external memory (USB)
- possibility to operate with exhaust fan module.
 control of fan and auger conveyor
- control of actuator of mixing valve as a standard
- control of actuator of mixing valve as a standa
 weekly programs
- control of central heating and domestic hot water pump
- . control of two additional pumps
- possibility to connect room controller with RS or conventional communication e.g. SPK LUX
- · possibility to connect DEFRO GSM module
- possibility to connect new version of DEFRO Internet module allowing remote change of boiler operation parameters (access to user and service menul via www.emodul.pl
- possibility to control two additional valves using DEFRO MZ modules
- servicing of motoreducer with reverse operation (not applicable to PZ version)
- · large colour graphical display
- touch panel
- adjustable angle of the screen, from 45°
 to 105°
- temperature sensor for central heating, domestic hot water, valve, additional, flue gas and external temperature
- · temperature protection (thermal overload relay)
- temperature sensor for endless screw (protection)
- high quality casing



APC 3 SLIM

CONTROLLER FUNCTIONS:

- innovative control system ADAPTIVE Control using turbine flow meter ensuring optimum selection of fan and feeder operation parameters
 fan control (testing of air flow necessary for
- correct combustion process) and feeder
- control of central heating and domestic hot water pump and valve
- control of auxiliary equipment
- · control of one mixing valve
- automatic firing up and damping a boiler
- · weekly programs
- control through the internet (remote firing up and damping) option
- possibility to connect room controller with RS or conventional communication
 option to connect the ST-65 GSM module
- firing up using a heater
- possibility to control additional mixing valve using DEFRO MZ module
- large colour graphical display
- controller panel located in the control desk
- with adjustable inclination angle

 temperature sensor for central heating, domestic hot water, valve, flue gas
- photoresistor (flame sensor)
- equipped with temperature protection for burner



MASTER 300 RS

CONTROLLER FUNCTIONS:

- maintenance of set boiler temperature by control of blowing and operation of the feeder
- option to add using RS modules extending regulator capacities:
- boiler weather compensation control and additional control of mixing valve
- modules (max. 3) controlling the mixing valve cooperating with separate thermostat
- set fan power
- programmable boiler blowing
- · adjusted extinguishing time and automatic
- shutdown of control when no fuel is available
 control of operation central heating circulating
- possibility to switch on or switch off priority of domestic hot water
- control of pump loading the domestic hot water heater depending on to the required temperature
- boiler and domestic hot water pump operation acc. to the one of weekly programs, installed in the regulator
- COMFORT SYSTEM function, protecting pump against deposition of scale
- · protection system thermal fuse
- function protecting the system against frosting and overheating of the boiler
- · signalling of temperature sensors damage
- adjustable brightness of the display increased when settings are changed
- possibility to connect local thermostat DK Logic 100



HG PID

CONTROLLER FUNCTIONS:

- · possibility to operate with exhaust fan module.
- control of fan and auger conveyor
 control of actuator of mixing valve as a stan-
- weekly programs

dard

- control of central heating and domestic hot water pump
- control of additional pump
- possibility to connect room controller with RS or conventional communication
- · possibility to connect DEFRO GSM module
- possibility to connect new version of DEFRO Internet module allowing remote change of boiler operation parameters

(access to user and service menu)

ROOM REGULATORS AND ADDITIONAL MODULES



DK MATIC

REGULATOR FUNCTIONS:

- control of heating circuit equipped with mixing valve with actuator
- boiler temperature control if it is adapted for such purpose or option to develop with 2 DKMZ modules for servicing of mixing valve with actuator
- adjustment of temperature of two circuits based on external temperature according to the selected heating curve
- possibility to select independent heating curve for the each circuit
- function of upward or downward displacement of curve for better adjustment to the thermal characteristic of the building
- function protecting the system against frosting and overheating of the boiler
- signalling of temperature sensors damage
- · co-operation with a room thermostat



ST-292 v3

REGULATOR FUNCTIONS:

- · room temperature control
- weekly heating plan
- day/night program
- manual program
- OptimumStart function selection of optimum time for boiler start-up to achieve thermal comfort to heat the room up to the set temperature for a previously set time
- heating/cooling function
- temporary display illumination
- built-in room sensor
- front panel made of glass 3mm
- · capacitive buttons



DKMZ

REGULATOR FUNCTIONS:

- control of second heating circuit equipped with 3/4 valve with actuator
- adjustment of temperature of two circuits based on external temperature according to the selected heating curve (after connecting to controller with external temperature sensor)
- possibility to select independent heating curve for the boiler and circuit with mixing valve
- function of upward or downward displacement of curve for better adjustment
- function protecting the system against frosting and overheating of the boiler
- · signalling of temperature sensors damage
- · co-operation with a room thermostat



ST-292 v2

REGULATOR FUNCTIONS:

- · wireless communication
- room temperature control
- weekly heating planday/night program
- · uay/riigiti progi
- manual program
- OptimumStart function selection of optimum time for boiler start-up to achieve thermal comfort to heat the room up to the set temperature for a previously set time
- heating/cooling function
- temporary display illumination
- built-in room sensor
- · wireless external sensor (additional option)
- floor temperature sensor (additional option)

T25;40°

LOGIC 100

REGULATOR FUNCTIONS:

- option to set various programmes for each day of the week
 two factory programmes
- · option to set own programme
- two temperatures for selection day and night
- six heating periods during the day
- · easy and intuitive programming method
- option of short-time changes of heating temperatures
 adjustable hysteresis from 0.1 °C to 2 °C
- temperature indication correction from -5 °C to +5 °C by 0.1 °C
- easy installation
- protection against frosting
- temperature adjustment by 0.1 °C
- · multifunctional display



DEFRO MZ

MODULE FUNCTIONS:

- · smooth control of actuator of three-way and four-way mixing valve
- control of pump operation
- · protection of return temperature
- weather compensated control
- · co-operation with a room controller
- cooperation with boiler controller through RS communication
- LCD display
- · valve temperature sensor
- return temperature sensor
- outside sensor
- housing made of high quality materials resistant to high and low temperatures



WIFI PK MODULE

MODULE FUNCTIONS:

- NO/NC relay output
- built-in temperature sensor
- on wired external sensor C-7 p
- · option to select sensor for module operation
- · supervision using web application www.emodul.pl



DEFRO SPK LUX

REGULATOR FUNCTIONS:

- · central heating boiler temperature control
- domestic hot water temperature control
- control of temperature of mixing valve
- room temperature control
- preview of the outside temperature
- weekly heating plan
- alarm clock
- parental lock
- displaying current boiler and room temperature waveforms
- display of alarms in the main controller of the boiler
- large, easy-to-read, colour, touch screen
- built-in room temperature sensor
- RS communication cable for the boiler controller

HEAT EXCHANGER CLEANING SYSTEM



AUTOMATICAL CLEANING

SYSTEM

MECHANICAL CLEANING SYSTEM

An improvement in form of heat exchanger cleaning was introduced to increase the comfort of boiler operation. Depending on boiler model it can be started manually - using a lever or automatically using electric drive. The system uses economizers in form of springs, located in boiler chimney draughts, which allow comfortable cleaning of heat exchanger walls. Furthermore, economizers cause flue gas swirling, what increases heat recovery from flue gas and limits emission of dusts to the atmosphere.

It is possible to program times and period of cleaning in case of the automatically started system.

The mechanical cleaning system is available as standard equipment in boilers:

- Sigma Ekopell
- Sigma E
- Defro Kompakt Ekopell
- HC

Automatic exchanger cleaning and ash removal system available as standard equipment in boilers:

- Alla
- Defro Kompakt Ekopell F

ADAPTIVE CONTROL SYSTEM

The innovative self-adapting control system adjusts boiler operation based on the amount of air flowing through the heat exchanger allowing precise feeding of air for combustion in relation to the fuel dose. The most important components of the system:

- turbine flowmeter with Hall sensor transferring signal to the controller related to the amount of air supplied for the combustion process.
- flue gases temperature sensor providing information about its current value.

Based on collected data boiler correspondingly adjusts the amount of air and fuel necessary for the combustion process to achieve temperature set by the user in an effective way. ADAPTIVE CONTROL system considerably improves the efficiency of the combustion process, what translates into a decrease of emission of pollution to the atmosphere. It considerably improves also increase of boiler servicing comfort by the elimination of necessity to adapt the operation parameters by the user depending on changing operating conditions.

FEEDER OVERLOAD PROTECTION SYSTEM

The driving system is equipped with motoreducer with installed Hall sensor, transmitting the information to the electronic controller about the current operation of the fuel, that is its revolutions and direction. If the endless screw is jammed the controller automatically switches the direction of revolutions (worm is withdrawn) for several seconds and then it attempts to overcome the obstacle. If the process is not successful then another two attempts will be undertaken. But, for each attempt, the motoreducer withdraws the worm two times longer. The solution eliminates the problem of troublesome replacement of security pin if the feeder is blocked.

TWIN SPARK SYSTEM (TSS)

TSS- TWIN SPARK SYSTEM

Innovative solution based on the use of two ceramic heaters in selected DEFRO boilers fired with a pellet. Correctly configured controller algorithm adjusts operation ensuring that they operate alternately. It means that only one heater is used for each firing up the process and it is used every second cycle. Use of the TSS system lengthens the time of service of the firing system two times. Furthermore, if one of the heaters is damaged then the second takes its function, what allows trouble-free start-up of the boiler. At the same time, the user is informed about the immediate replacement of the damaged component.

FUEL LEVEL CONTROL SYSTEM

Revolutionary fuel level control system cooperating with a capacitive sensor. If the minimum, factory-specified fuel level in the container is detected, the sensor stops boiler operation, and the user gets information about the necessity to add the fuel. An unquestionable advantage of the system it possibility of automatic start-up of the boiler after recharging the fuel.

MAX SERIES BOILERS 50 - 900 kW



EkoPell Max F 300-800 kW

- version with automatic cleaning and ash removal (extra payable according to the price list of boiler equipment)

Each boiler may be adapted by our construction department to the requirements of the project, both with respect to technical issues, equipment and automation. Technical data of boilers is available on the request, after determination of execution version.

It is possible to adapt the boiler for the individual needs of the customer.

EKOPELL MAX Fuel: wood pellet with diameter 6-8 mm				
POWER	PRODUCT TYPE	5th CLASS	ECODESIGN	
75 kW	В	✓	✓	
100 kW	В	✓	-	
150 kW	В	✓	✓	
200 kW	В	✓	-	
250 kW	В	✓	-	
300 kW	В	✓	✓	

it is possible to deapt the boiler for the maintenant riceas of the destorner.				
EKO MAX Fuel: eco-pea coal 5-25 mm				
POWER	PRODUCT TYPE	5th CLASS	ECODESIGN	
75 kW	В	✓	✓	
100 kW	В	✓	-	
150 kW	В	✓	✓	
200 kW	В	✓	-	
250 kW	В	✓	-	
300 kW	В	✓	✓	





DISTRIBUTOR

hhh.

Manufacturer: DEFRO Spólka z ograniczoną odpowiedzialnością Spólka komandytowa registered office: 00-403 Warszawa, ul. Solec 24/253, National Court Register: 0000620901, TIN: 9591968493, REGON: 363378898

Address for correspondence/production plant: 26-067 Strawczyn, Ruda Strawczyńska 103A tel. 41 303 80 85, fax: 41 303 91 31, e-mail: biuro@defro.pl

Current prices of the products are available from the DEFRO authorized distributors or in authorized points of sales. List of authorized points of sales is available at www.defro.pl. The catalogue includes suggested retail prices.

Validity period: 01.03.2019-31.03.2019

